



https://www.hcfa.cn

访问官网或扫描二维码下载最新版安装使用说明书

Download the latest installation sheets via the official website or QR code.

浙江禾川科技股份有限公司
浙江省衢州市龙游县工业园区亲善路5号

Zhejiang Hechuan Technology Co., Ltd
No.5, Qinshan Road, Longyou Industrial Zone, Quzhou City, Zhejiang Province



07060201-0816-001
Date 2025-07-29
CN 安装说明
EN Instruction Sheet

1. 安全注意事项 (Safety precautions)

本说明书涉及产品为工业产品，并且均为开放型外壳设计。要求用户使用产品时，务必将产品安装于具有防尘、防潮以及免于电击 / 冲击等意外的控制柜内，并且需要设置保护措施以防止非维护人员不当操作或意外导致设备故障或损坏，造成不可避免的人员危险和财产损失。

The products in this manual are industrial products and are all open-type housing designs. It is essential to install these products within a control cabinet that is safeguarded against dust, moisture, and accidents such as electric shocks or physical impacts. Additionally, protective measures must be taken to prevent malfunctions or damage caused by improper operation or accidents involving non-maintenance personnel. Failure to do so may lead to serious risks to personnel safety and potential loss of property.

更详细的信息请参考 QP 系列硬件手册。

Please refer to the QP series hardware manual for more detailed information.

⚠️ Battery	QP 系列弹片式电池型号为 CR2032 (3.2V)，客户可自行选购符合 UL 认证且规格参数合适的电池，由专业的电气工程师佩戴绝缘手套在断电情况下参考 5.3 小节描述进行电池更换。
	For the spring-contact battery, its model number is CR2032 (3.2V), customers can choose batteries that meet UL certification and have appropriate specifications on their own. Professional electrical engineers will wear insulated gloves to replace the batteries in the event of a power outage, as described in section 5.3.
	Pour la pile à contact à ressort, son numéro de modèle est CR2032 (3.2V), Les clients peuvent acheter eux-mêmes des batteries conformes à la certification UL et aux paramètres de spécification appropriés, qui seront remplacées par des ingénieurs électriciens professionnels portant des gants isolants en cas de panne de courant, en se référant à la description de la Sous-section 5.3.

2. 命名规则 (Model identification)

HC Q3 P - 1 4 0 0 - D 4 - XXXX
1 2 3 4 5 6 7 8 9 10

1	产品名称 (Product name)
HC	禾川 (Hechuan Technology)
2	产品系列 (Product series)
Q3	高端总线型运动控制器 (High-end Bus-based motion controller)
3	系列型号 (Series type)
空 (N/A)	标准型 (Standard type)
P	增强型 (Enhanced type)

4	操作系统 (Operating system)
1	Linux
5	内部编号 (Internal number)
4	预留 (Reserved)
6	控制软件模块 (Control software module)
0	CODESYS
7	控制软件 (Control software)
0	标准软件 (Standard software)

8	电源类型 (Power supply type)
D	直流电源 (DC power supply)
9	迭代版本 (Iteration version)
4	第4代 (The 4th generation)
10	软件/固件定制代码 (Customized software/firmware code)
X	0~9/A~Z/空 (N/A)

3. 适用型号 (Applicable model)

名称 (Name)	型号 (Model)	适配的 IO 型号* (Applicable IO model)	简要说明 (Brief description)
CPU单元 CPU unit	HCQ3P-1400-D4	HCQX-EC01-D4 HCQX-EC02-D4 HCQX-EC03-D4 HCQX-ES06-D4 HCQX-ID16-D4 HCQX-OD16-D4 HCQX-OD16-D4-PNP HCQX-MD16-D4 HCQX-MD16-D4-PNP HCQX-ID32-D4 HCQX-OD32-D4 HCQX-OD32-D4-PNP HCQX-MD32-D4 HCQX-MD32-D4-PNP HCQX-AD04-D4 HCQX-DA04-D4 HCQX-TS04-D4 HCQX-RS02-D4 HCQX-RS02-D4-M HCQX-OC08-D4	ARM处理器、8G EMMC、运存512M、掉电保持区1M、16点输入16点输出、32轴EtherCAT总线、8轴脉冲、2路以太网口、1路EtherCAT口、RS485*2、RS232*1、CAN*1、USB-A*1、USB-C*1、SD卡*1 ARM processor, 8G EMMC, 512M RAM, 1M persistent data memory, 16-channel input and 16-channel output, 32-axis EtherCAT bus, 8-axis pulse, 2-channel Ethernet port, 1-channel EtherCAT port, RS485*2, RS232*1, CAN*1, USB-A*1, USB-C*1, SD card*1 支持协议 (Supported protocols) : Modbus RTU, Modbus TCP, EtherCAT, CANopen, EtherNet/IP, OPC UA

*注：CPU 单元右侧可挂载模块数量以实际功率计算。

*Note: The number of modules that can be mounted on the right side of the CPU unit is calculated based on the actual power.

4. 通用电气及环境规格 (General electrical and environmental specifications)

4.1 通用电气规格 (Electrical specifications)

型号 (Model)*1	额定电压 / 功率 (Rated voltage/power)*2	输出电压 / 功率 (Output voltage/power)	数字量输入 / 输出类型 (Digital input/output type)
HCQ3P-1400-D4	DC24V (DC 20.4V~28.8V)/32W	DC12V/16W	数字量输入 (Digital input) : DC24V, 6.81mA/Ch 芯片输出 (Digital output) : DC24V, 500mA/Ch, 4A/16Ch*3 负载类型: 阻性/电磁负载 (Resistive/Pilot duty)

*注：1. 所有型号仅能在由有限功率电源 (LPS) 提供的安全特低电压 (SELV) 下运行。

2. 此处标识的额定功率为满负载运行时的最大功率。

3. 考虑温升影响，降额使用。








*Note: 1. All models can only operate under the safety extra low voltage (SELV) provided by a limited power source (LPS).

2. The power rating indicated here is the maximum power under full-load operation.


3. Consider the effect of temperature rise and derate during using.

4.2 环境规格 (Environmental requirements)

项目	Item	规格	Specifications
海拔高度	Altitude	≤2000m	≤2000m
使用环境	Operating environment	控制柜内安装，开放式及室内使用	Installation within a control cabinet, open-type and indoor use
工作温度	Operating temperature	-10~55℃	-10~55℃
储存温度	Storage temperature	-40~75℃	-40~75℃
环境湿度	Ambient humidity	10~95%RH (无结露)	10~95%RH (non-condensing)
振动耐受	Vibration resistance	5~150Hz (X/Y/Z方向, 1g/3.5mm位移)	5~150Hz (X/Y/Z direction, 1g/3.5mm displacement)
污染等级	Pollution degree	污染度2	Level 2
冷却方式	Cooling method	自然冷却	Natural cooling

控制器端子 (Terminal)		线径范围: AWG (Wire width)	剥线长度: mm (Wire stripping length)	按压力: N (Pressure)	
DC24V 电源端子 (DC24V power supply terminal)		24~16	9~10	12	
5.6 线缆拆装 2 (Cable connecting and disconnecting II)					
CN	安装线缆时, 将一字螺丝刀垂直插入 18Pin IO 端子压块内, 施加超过 30N 的力, 此时圆孔打开, 将准备好的线缆插入到圆孔中, 拔出一字螺丝刀, 轻拽线缆, 线缆不松动即成功完成配线, 反之即可取出线缆。端子规格及配线示意图如右图所示。				
EN	During connecting, insert the flat-blade screwdriver into the 18Pin IO terminal unlocking tab with a force of more than 30N. Then insert a cable into the circular hole. Gently tug the cable after pulling out the screwdriver. If the cable is secured firmly, then the connection is finished. The reverse is the procedure for unplugging the cable. The terminal specifications and wiring diagram are shown in the right figure.				
控制器端子 (Terminal)		线径范围: AWG (Wire width)	剥线长度: mm (Wire stripping length)	按压力: N (Pressure)	
18Pin IO端子 (18Pin IO terminal)		24~18	8~10	30	
5.7 线缆拆装 3 (Cable connecting and disconnecting III)					
CN	安装线缆时, 将一字螺丝刀垂直插入 12Pin 通讯端子压块内, 施加超过 16N 的力, 此时圆孔打开, 将准备好的线缆插入到圆孔中, 拔出一字螺丝刀, 轻拽线缆, 线缆不松动即成功完成配线; 反之即可取出线缆。				
EN	During connecting, insert the flat-blade screwdriver into the 12Pin communication terminals unlocking tab with a force of more than 16N. Then insert a cable into the circular hole. Gently tug the cable after pulling out the screwdriver. If the cable is secured firmly, then the connection is finished. The reverse is the procedure for unplugging the cable. The terminal specifications and wiring diagram are shown in the right figure.				
控制器端子 (Terminal)		线径范围: AWG (Wire width)	剥线长度: mm (Wire stripping length)	按压力: N (Pressure)	
12Pin通讯端子 (12Pin communication terminal)		28~16	8~9	16	
警告: 只能使用 75°C铜导线。 Warning: Use only a copper conductor that is 75° C. Attention: Utilisez uniquement un conducteur en cuivre à 75° C.					

6. 接口和尺寸说明 (Interface and dimension description)



序号 (No.)	名称	Name	功能	Function
1	前翻盖	Front flip cover	保护内部指示灯与端子	Protects the indicators and terminals
2	数码管	LED	显示系统运行状态和报错代码	Displays system operation status and error code
3	Type-C接口	Type-C interface	预留接口	Reserved interface
4	指示灯	Indicator	显示控制器运行, SD卡/U盘连接与通讯接口状态	Displays the status of controller operation, SD card/U disk connection, and communication interface
5	SD卡槽	SD card slot	支持Micro SD卡插入, 用于数据存储, 程序导入导出	Supports Micro SD card insertion for data storage, program import, and export
6	USB-A接口	USB-A interface	支持U盘导入/导出程序与文件读写, 支持DC5V/1A供电	Supports U disk program import/export and file reading/writing, supports DC5V/1A power supply
7	DC24V电源端子	DC24V power supply terminal	DC24V供电接口	DC24V power supply interface
8	COM1终端电阻开关	COM1 termination resistor switch	向上拨动为开启终端电阻, 向下拨动为关闭终端电阻, 出厂默认关闭状态	Toggle up to turn on the terminating resistor, toggle down to turn off the terminating resistor, off by factory default
9	COM2终端电阻开关	COM2 termination resistor switch		
10	CAN终端电阻开关	CAN termination resistor switch		
11	STOP/RUN/FN 拨码开关	STOP/RUN/FN dial switch	功能拨码, 向左为控制器停止状态, 中间为运行状态, 向右拨至FN并停留3s为恢复Port1/port2 IP默认值	DIP switch. Toggle to the left to put the controller in the STOP state. Toggle to the center to put it in the RUN state. Toggle to the right to put it to the FN state for 3s to restore the IP addresses of Port1/port2 to the default value
12	12Pin通讯端子	12Pin communication terminal	RS485/RS232/CAN通讯接口	RS485/232/CAN communication interface
13	双向联动卡扣	DIN rail mounting latch	固定模块在DIN导轨上	Mounts the module onto a DIN rail

14	产品型号		Product model		显示CPU单元型号	Displays CPU unit model
15	模块状态指示灯		Module status indicator		显示模块与通道状态	Displays module and channel status
16	18Pin IO端子	左侧 输入	18Pin IO terminal	Left input	16通道数字量输入	16-channel digital input
		右侧 输出		Right output	16通道数字量输出	16-channel digital output
17	RJ45 通讯接口	Port1 EtherNet	RJ45 communication interface	Port1 EtherNet	千兆以太网口，支持Modbus TCP、OPC UA、EtherNet/IP Scanner和Adapter Port1 IP: 192.168.188.100	Gigabit Ethernet port, supports Modbus TCP, OPC UA, EtherNet/IP Scanner and Adapter Port1 IP: 192.168.188.100
		Port2 EtherNet		Port2 EtherNet	千兆以太网口，支持Modbus TCP、OPC UA、EtherNet/IP Scanner和Adapter Port2 IP: 192.168.88.100	Gigabit Ethernet port, supports Modbus TCP, OPC UA, EtherNet/IP Scanner and Adapter Port2 IP: 192.168.88.100
		Port3 EtherCAT		Port3 EtherCAT	百兆以太网口，支持EtherCAT主站	Fast Ethernet port, supports EtherCAT master
18	RTC电池		RTC battery		维持部分系统参数	Maintains part of the system parameters
19	金属弹片（悬空）		Metal spring (float)		无功能，预留接口	No function, reserved interface
20	扩展模块通讯接口		Expansion terminal communication interface		主机和IO模块通讯及供电接口，不支持热插拔	The interface for the communication and power supply of the host and IO modules, does not support hot-swapping
21	标签		Label		显示CPU单元型号，规格参数、内部序列号等基本信息	Displays the basic information including CPU unit model, specification parameters, and internal serial number

型号 (Model)	外形尺寸 (Dimension) : mm									重量 (Weight) : g
	W1	W2	W3	H1	H2	H3	H4	D1	D2	
HCQ3P-1400-D4	132.2	127.9	24.4	104.5	100.0	105.5	35.4	82.0	74.5	816 approx.

7. 指示灯说明 (Indicator description)

		数码管 (LED)		状态	Status	说明	Description
				开机	Boot	开机中	Booting up
				Run	Run	正常运行	Run
				Stop	Stop	停止	Stop
				报错	Error	错误代码	Error code
丝印 (Screen printing)	指示灯含义 (Indicator meaning)	颜色 (Color)	状态	Status	说明	Description	
SYS	系统状态 (System status)	红色	Red	其他	Other	发生故障	Error
				闪烁	Blinking	正常运行	Run
SD_BUSY	SD 卡 / U 盘 (SD card/U disk)	红色	Red	熄灭	Not lit	SD 卡 / U 盘安全卸载或全部拔出	Uninstall or unplug the SD card /USB flash drive successfully
				常亮	Lit	成功加载 SD 卡 / U 盘	Load the SD card /USB flash drive successfully
CAN *	CANOpen 通讯 (CANOpen communication)	-	-	-	-	-	-
COM1	RS485 通讯 (RS485 communication)	TX 绿色	Green	熄灭	Not lit	未发送数据	No data is being sent to other devices
COM2				闪烁	Blinking	正在发送数据给其他设备	Data is being sent to other devices
COM3	RS232 通讯 (RS232 communication)	RX 红色	Red	熄灭	Not lit	未接收数据	No data is being received from other devices
				闪烁	Blinking	正在接收其他设备发送的数据	Data is being received from other devices
QBUS L/A	QBUS 通讯 (QBUS communication)	黄色	Yellow	熄灭	Not lit	通讯断开 / 故障	Communication is abnormal or disconnected
				闪烁	Blinking	通讯正常	Communication is normal
IN N (0~7,10~17)	输入 (Input)	绿色	Green	熄灭	Not lit	输入通道 N 未检测到输入信号	The input channel N has not detected input signals
				常亮	Lit	输入通道 N 检测到输入信号	The input channel N has detected input signals
OUT N (0~7,10~17)	输出 (Output)	绿色	Green	熄灭	Not lit	输出通道 N 无信号输出	There is no output signal in this channel
				常亮	Lit	输出通道 N 有信号输出	There are output signals in this channel
EtherNet EtherCAT	LINK 物理连接 (Physical connection)	绿色	Green	熄灭	Not lit	未建立物理连接	Physical connection has not been established
				常亮	Lit	已建立物理连接	Physical connection has been established
	ACT 数据交互 (Data exchange)	黄色	Yellow	熄灭	Not lit	未收发数据	No data is being sent or received
				闪烁	Blinking	正在收发数据	Data is being sent or received

* 注：后续支持。
*Note: It will be supported subsequently.


8. 端子及配线说明 (Terminal and wiring description)

DC24V 电源端子说明 (DC24V power supply terminal description)		接线 (Wiring)
24V		
0V		
地		


18Pin IO 端子说明 (18Pin IO terminal description)		IN		OUT		类型 (Type)	通用IO接线 (General IO wiring)	高速IO接线 (High-speed IO wiring)
0		10	I0	I10	Q0	Q10	开关 Switch 漏型输入 NPN Input	编码器 Encoder 屏蔽层 Shield
1		11	I1	I11	Q1	Q11		
2		12	I2	I12	Q2	Q12		
3		13	I3	I13	Q3	Q13	开关 Switch 源型输入 PNP Input	编码器 Encoder 屏蔽层 Shield
4		14	I4	I14	Q4	Q14		
5		15	I5	I15	Q5	Q15		
6		16	I6	I16	Q6	Q16	负载 Load 漏型输出 NPN Output	脉冲PLS_out
7		17	I7	I17	Q7	Q17		
8		18	SS ⁺	SS ⁺	COM ⁺	COM ⁺		

* 注：输入公共端 SS 内部导通，输出公共端 COM 内部导通。
 *Note: The input terminals SS are internally conductive, and so are the output terminals COM.


12Pin通讯端子说明 (12Pin communication terminal description)												
定义 (Definition)	A1	B1	SG	A2	B2	SG	TX	RX	SG	H	L	SG
接口 (Interface)	COM1			COM2			COM3			CAN		




COM1/COM2 RS485接线 (RS485 Wiring)



COM3 RS232接线 (RS232 Wiring)



CAN CANOpen接线 (CANOpen Wiring)



* 注：内置终端电阻，通过终端电阻拨码开关启用。
 *Note: Built-in terminating resistor, which is enabled by the terminating resistor DIP switch.